

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER : 05261799
PUBLICATION DATE : 12-10-93


APPLICATION DATE : 17-03-92
APPLICATION NUMBER : 04090133

APPLICANT : DENKI KAGAKU KOGYO KK;

INVENTOR : KAWACHI KOICHI;

INT.CL. : B29C 49/08 B29C 49/12 B29C 49/66 //
B29L 22:00

TITLE : METHOD FOR MOLDING RESIN
HOLLOW CONTAINER



ABSTRACT : PURPOSE: To obtain a molding method for preventing occurrence of residual stress and obviating the need for second dehydration of a hollow container by a method wherein just before the mold opening after the retraction of a drawing rod, the container is cooled by jetting a cooling gas out of cooling gas jet ports connecting to a cooling gas feed tube.

CONSTITUTION: In a method for blow molding a resin hollow container 1, a previously molded parison is put in a heated mold 3, a drawing rod 7 is brought into contact with the bottom of the parison, the parison is vertically drawn by moving the drawing rod 7 downward, a mandrel 9 for blow molding is inserted into a neck part of the parison, the parison is laterally drawn by jetting a compressed fluid through a pressurized fluid path 11 provided in the mandrel 9, and the parison is cooled and released from the mold. Just before the mold 3 opens after the drawing rod 7 is retracted, the container 1 is cooled by jetting a 10-50°C cooling gas out of a plurality of cooling gas jet ports 13 connecting to a cooling gas feed tube 10 provided in the hollow drawing rod 7.

COPYRIGHT: (C)1993,JPO&Japio